

TE0729 Resources

TE0729 - 5.2 x 7.6 cm SoC module with Xilinx Zynq-7020

- [TE0729](#) - Wiki with TRM, reference projects, application notes and more
 - [TE0729 TRM](#) - Technical Reference Manual
 - [TE0729 CPLD Firmware](#) - Firmware Description
- [5.2 x 7.6 SoM BTE and BSE B2B Connectors](#) - overview, compatibility, mating heights and speed rating

Links

- [Shop TE0729](#) - contains prices, available stock, disposability, scope of delivery and more
- [Download area](#) - various reference designs, schematics, hardware designs and more
- [Pinout/Tracelength Table](#) - illustration of pinout, tracelength and cross reference Information of modules with different baseboards

5.2 x 7.6 Carrier

- [5.2 x 7.6 Carriers](#) - overview of available carrier boards for all 5.2 x 7.6 cm SoM modules

Notes



Watchdog does not work correctly on all modules with Firmware released before 2017.08.22. Please update Firmware on CPLD. For questions, write to Trenz Electronic support.



2 Firmware variants with swapped external reset input and output direction are available. See [Watchdog](#) section of this document. Firmware for J2-89 as external reset output and J2-91 as external reset input will be used as default firmware.

Support

- For support, please go to <http://forum.trenz-electronic.de/> or contact support@trenz-electronic.de