

COM-HPC Carriers

Table of Content

- [Table of Content](#)
- [Legend](#)
- [TEBT0830 - Micro-ATX\(244 mm x 244 mm\) Test Carrier for COM-HPC Client Size C and Server Size D Modules\(1\)](#)

Legend

- ⚠️ : Attention: Carrier/Module combination only with special condition or PCB modification possible
- ✅ : Supported
- ⭐ : Supported with limitations
- ❌ : Not Supported
- ❓ : Table currently not complete, see TRM of module and carrier

TEBT0830 - Micro-ATX(244 mm x 244 mm) Test Carrier for COM-HPC Client Size C and Server Size D Modules⁽¹⁾

Module /Carrier Connectors	TE0790 USB (Xilinx JTAG /UART)	TEI0004 (Intel JTAG /UART)	Gbit Ethernet	USB 3 / USB 2	DisplayPort	WIFI M. 2	FireFly	I2C	SPI	GPIO	PMOD	Switches (x4)	Buttons
	• UART0	• connect to UART1	• 1x	• 2x	• 1x	• 1x	• PCUOPC le • 2x	• 2, 5 4 mm • 4x	• 2, 5 4 mm • 3x	• x Pins	• 2x	• 2x	• 2x
TE0830	✅	✅	❓	❓	❓	❓	❓	❓	❓	❓	❓	❓	❓

- (1) Primary developed for FGPA based COM-HPC modules
- (2) UART only, module is without Xilinx device