

TEF0008 MAX10

Table of contents

- 1 [Table of contents](#)
- 2 [Overview](#)
 - 2.1 [Feature Summary](#)
 - 2.2 [Firmware Revision and supported PCB Revision](#)
- 3 [Product Specification](#)
 - 3.1 [Port Description](#)
 - 3.2 [Functional Description](#)
 - 3.2.1 [SFP Control](#)
 - 3.2.2 [I2C](#)
 - 3.2.3 [LED](#)
 - 3.2.4 [JTAG](#)
- 4 [Appx. A: Change History and Legal Notices](#)
 - 4.1 [Document Change History](#)
 - 4.2 [Revision Changes](#)
 - 4.3 [Legal Notices](#)
 - 4.4 [Data Privacy](#)
 - 4.5 [Document Warranty](#)
 - 4.6 [Limitation of Liability](#)
 - 4.7 [Copyright Notice](#)
 - 4.8 [Technology Licenses](#)
 - 4.9 [Environmental Protection](#)
 - 4.10 [REACH, RoHS and WEEE](#)

Overview

TEF0008 design for MAX10 FPGA U2: 10M08SAU169C8G.

Feature Summary

- SFP Control
- I²C MUX
- level shifter
- LED Control

Firmware Revision and supported PCB Revision

See Document Change History.

Product Specification

Port Description

Name / opt. VHD Name	Direction	Pin	weak pullup	Description
PLL_SDA_io	Bidir	K2		I ² C Si5345A-B
PLL_SCL_o	Out	K1		I ² C Si5345A-B

LED	Out	C2		Status LED
A_LOS_i	In	H9		SFP A Signal Loss (HIGH indicates signal loss)
A_MDEF0_i	In	G9		SFP A Module Absent (HIGH when module physically absent)
A_RS0_o	Out	J9		SFP A Rate Select RX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
A_RS1_o	Out	H8		SFP A Rate Select TX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
A_SCL_o	Out	K10		SFP A I ² C Clock
A_SDA_io	Bidir	K11		SFP A I ² C Data
A_TX_DIS_o	Out	H10		SFP A (HIGH disables transmitter)
A_TX_FAULT_i	In	L12		SFP A Laser Fault (HIGH indicates fault)
B_LOS_i	In	K12		SFP B Signal Loss (HIGH indicates signal loss)
B_MDEF0_i	In	J13		SFP B Module Absent (HIGH when module physically absent)
B_RS0_o	Out	J12		SFP B Rate Select RX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
B_RS1_o	Out	L13		SFP B Rate Select TX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
B_SCL_o	Out	H13		SFP B I ² C Clock
B_SDA_io	Bidir	G10		SFP B I ² C Data
B_TX_DIS_o	Out	G13		SFP B (HIGH disables transmitter)
B_TX_FAULT_i	In	G12		SFP B Laser Fault (HIGH indicates fault)
C_LOS_i	In	F12		SFP C Signal Loss (HIGH indicates signal loss)
C_MDEF0_i	In	E12		SFP C Module Absent (HIGH when module physically absent)
C_RS0_o	Out	F13		SFP C Rate Select RX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
C_RS1_o	Out	F9		SFP C Rate Select TX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
C_SCL_o	Out	E13		SFP C I ² C Clock
C_SDA_io	Bidir	D11		SFP C I ² C Data
C_TX_DIS_o	Out	D12		SFP C (HIGH disables transmitter)
C_TX_FAULT_i	In	C12		SFP C Laser Fault (HIGH indicates fault)
D_LOS_i	In	B11		SFP D Signal Loss (HIGH indicates signal loss)
D_MDEF0_i	In	B12		SFP D Module Absent (HIGH when module physically absent)
D_RS0_o	Out	B13		SFP D Rate Select RX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
D_RS1_o	Out	C13		SFP D Rate Select TX (LOW for 1000BASE-SX, HIGH for 10GBASE-SR)
D_SCL_o	Out	A12		SFP D I ² C Clock
D_SDA_io	Bidir	F10		SFP D I ² C Data
D_TX_DIS_o	Out	E9		SFP D (HIGH disables transmitter)
D_TX_FAULT_i	In	D9		SFP D Laser Fault (HIGH indicates fault)
LA00_P	In	M9	ON	SCL In
LA00_N	In	N5	ON	SDA In
LA01_P	Out	L4		SDA Out
LA01_N	In	J5	ON	I2C MUX 0: SEL[0]
LA02_P	In	M13	ON	I2C MUX 1: SEL[1]
LA02_N	In	M12	ON	I2C MUX 2: SEL[2]

LA03_N	In	N6	ON	RS0
LA03_P	In	M5	ON	TX_DISABLE
LA04_N	Out	K7		TX Fault A+B+C+D
LA04_P	In	J7	ON	RS1
LA05_N	Out	L5		LOS A
LA05_P	Out	K5		DEF0 A, SFP A Inserted Flag
LA06_N	Out	J6		LOS B
LA06_P	Out	K6		DEF0 B, SFP B Inserted Flag
LA07_N	Out	M8		LOS C
LA07_P	Out	N8		DEF0 C, SFP C Inserted Flag
LA08_N	Out	M7		LOS D
LA08_P	Out	N7		DEF0 D, SFP D Inserted Flag
LA09_P	-	N4		/currently unused
LA09_N	-	M4		/currently unused

Functional Description

SFP Control

- Input Signal LA03_N sets all four SFP RX modes (LA03_N=HIGH sets RS0 signals LOW for 1000BASE-SX, LA03_N=LOW sets RS0 signals HIGH for 10GBASE-SR)¹
- Input Signal LA04_P sets all four SFP TX modes (LA04_P=HIGH sets RS1 signals LOW for 1000BASE-SX, LA04_P=LOW sets RS1 signals HIGH for 10GBASE-SR)¹
- Output Signals LA05_N, LA06_N, LA07_N and LA08_N indicate signal loss of SFP A, B, C and D respectively (HIGH indicates signal loss).
- Output Signals LA05_P, LA06_P, LA07_P and LA08_P indicate SFP A, B, C and D module absent (HIGH when module physically absent).
- Output Signal LA04_N is HIGH when at least one of the four SFPs indicate Laser fault.
- Input LA03_P HIGH sets for all SFPs where the module is physically available (MDEF0_i is LOW) the TX_DIS signal to LOW.¹

¹Inverted control as we can not enable weak pulldown in MAX10, we use weak pullup. E.g. TX are all ENABLED at default power up, so the card is working with no FMC LA pin driven.

I²C

- LA00_P, LA00_N and LA01_P form a "three wire I²C" bus with separate data in and output.
- LA01_N, LA02_P and LA02_N are used as selector for the MUX.

SEL	I ² C device
000	SFP A
001	SFP B
010	SFP C
011	SFP D
100	Si5345 Clock Generator

For I2C addresses see [TEF0008 TRM](#).

LED

LED is used as Status LED and is on if at least on SFP is connected.

JTAG

MAX10 JTAG for programming is always enabled and accessible via the FMC connector, pin header J3 and test points.

Appx. A: Change History and Legal Notices

Document Change History

To get content of older revision go to "Change History" of this page and select older document revision number.

Revision Changes

Date	Document Revision	CPLD Firmware Revision	Supported PCB Revision	Authors	Description
		REV01	REV01, REV02	<div>Error rendering macro 'page-info' Ambiguous method overloadin g for method jdk. proxy279.\$ Proxy4022 #hasConte ntLevelPer mission. Cannot resolve which method to</div>	<ul style="list-style-type: none">added weak pullup column in port description tableclarified functional description sectioncorrected some typos

Error rendering macro 'page-info'

Ambiguous method
overloading for method jdk.
proxy279.\$Proxy4022#hasCon
tentLevelPermission. Cannot
resolve which method to
invoke for [null, class java.lang.
String, class com.atlassian.
confluence.pages.Page] due
to overlapping prototypes
between: [interface com.
atlassian.confluence.user.
ConfluenceUser, class java.
lang.String, class com.
atlassian.confluence.core.
ContentEntityObject] [interface
com.atlassian.user.User, class
java.lang.String, class com.
atlassian.confluence.core.
ContentEntityObject]

Error rendering macro 'page-info'

Ambiguous method
overloading for method jdk.
proxy279.\$Proxy4022#hasCon
tentLevelPermission. Cannot
resolve which method to
invoke for [null, class java.lang.
String, class com.atlassian.
confluence.pages.Page] due
to overlapping prototypes
between: [interface com.
atlassian.confluence.user.
ConfluenceUser, class java.
lang.String, class com.
atlassian.confluence.core.
ContentEntityObject] [interface
com.atlassian.user.User, class
java.lang.String, class com.
atlassian.confluence.core.
ContentEntityObject]

invoke for
[null, class
java.lang.
String,
class com.
atlassian.
confluence
.pages.
Page] due
to
overlappin
g
prototypes
between:
[interface
com.
atlassian.
confluence
.user.
Confluenc
eUser,
class java.
lang.
String,
class com.
atlassian.
confluence
.core.
ContentEn
tityObject]
[interface
com.
atlassian.
user.User,
class java.
lang.
String,
class com.
atlassian.

				<div>confluence .core. ContentEntityObject]</div>	
2018-08-27	v.05	REV01	REV01, REV02	Martin Rohrmüller	<ul style="list-style-type: none">• Added Legal Notices• some typos• small rearrangements
2018-08-07	v.03	REV01	REV01	John Hartfiel	<ul style="list-style-type: none">• small style update
2018-06-07	v.01	REV01	REV01	Martin Rohrmüller	<ul style="list-style-type: none">• initial document
	All			<div>Error rendering macro 'page-info' Ambiguous method overloading for method jdk. proxy279.\$ Proxy4022 #hasContentLevelPer mission. Cannot resolve which method to invoke for [null, class</div>	

java.lang.
String,
class com.
atlassian.
confluence
.pages.
Page] due
to
overlappin
g
prototypes
between:
[interface
com.
atlassian.
confluence
.user.
Confluenc
eUser,
class java.
lang.
String,
class com.
atlassian.
confluence
.core.
ContentEn
tityObject]
[interface
com.
atlassian.
user.User,
class java.
lang.
String,
class com.
atlassian.
confluence
.core.

				ContentEn tityObject]	
--	--	--	--	--------------------------	--

Legal Notices

Data Privacy

Please also note our data protection declaration at <https://www.trenz-electronic.de/en/Data-protection-Privacy>

Document Warranty

The material contained in this document is provided "as is" and is subject to being changed at any time without notice. Trenz Electronic does not warrant the accuracy and completeness of the materials in this document. Further, to the maximum extent permitted by applicable law, Trenz Electronic disclaims all warranties, either express or implied, with regard to this document and any information contained herein, including but not limited to the implied warranties of merchantability, fitness for a particular purpose or non infringement of intellectual property. Trenz Electronic shall not be liable for errors or for incidental or consequential damages in connection with the furnishing, use, or performance of this document or of any information contained herein.

Limitation of Liability

In no event will Trenz Electronic, its suppliers, or other third parties mentioned in this document be liable for any damages whatsoever (including, without limitation, those resulting from lost profits, lost data or business interruption) arising out of the use, inability to use, or the results of use of this document, any documents linked to this document, or the materials or information contained at any or all such documents. If your use of the materials or information from this document results in the need for servicing, repair or correction of equipment or data, you assume all costs thereof.

Copyright Notice

No part of this manual may be reproduced in any form or by any means (including electronic storage and retrieval or translation into a foreign language) without prior agreement and written consent from Trenz Electronic.

Technology Licenses

The hardware / firmware / software described in this document are furnished under a license and may be used /modified / copied only in accordance with the terms of such license.

Environmental Protection

To confront directly with the responsibility toward the environment, the global community and eventually also oneself. Such a resolution should be integral part not only of everybody's life. Also enterprises shall be conscious of their social responsibility and contribute to the preservation of our common living space. That is why Trenz Electronic invests in the protection of our Environment.

REACH, RoHS and WEEE

REACH

Trenz Electronic is a manufacturer and a distributor of electronic products. It is therefore a so called downstream user in the sense of [REACH](#). The products we supply to you are solely non-chemical products (goods). Moreover and under normal and reasonably foreseeable circumstances of application, the goods supplied to you shall not release any substance. For that, Trenz Electronic is obliged to neither register nor to provide safety data sheet. According to present knowledge and to best of our knowledge, no [SVHC \(Substances of Very High Concern\) on the Candidate List](#) are contained in our products. Furthermore, we will immediately and unsolicited inform our customers in compliance with REACH - Article 33 if any substance present in our goods (above a concentration of 0,1 % weight by weight) will be classified as SVHC by the [European Chemicals Agency \(ECHA\)](#).

RoHS

Trenz Electronic GmbH herewith declares that all its products are developed, manufactured and distributed RoHS compliant.

WEEE

Information for users within the European Union in accordance with Directive 2002/96/EC of the European Parliament and of the Council of 27 January 2003 on waste electrical and electronic equipment (WEEE).

Users of electrical and electronic equipment in private households are required not to dispose of waste electrical and electronic equipment as unsorted municipal waste and to collect such waste electrical and electronic equipment separately. By the 13 August 2005, Member States shall have ensured that systems are set up allowing final holders and distributors to return waste electrical and electronic equipment at least free of charge. Member States shall ensure the availability and accessibility of the necessary collection facilities. Separate collection is the precondition to ensure specific treatment and recycling of waste electrical and electronic equipment and is necessary to achieve the chosen level of protection of human health and the environment in the European Union. Consumers have to actively contribute to the success of such collection and the return of waste electrical and electronic equipment. Presence of hazardous substances in electrical and electronic equipment results in potential effects on the environment and human health. The symbol consisting of the crossed-out wheeled bin indicates separate collection for waste electrical and electronic equipment.

Trenz Electronic is registered under WEEE-Reg.-Nr. DE97922676.

Error rendering macro 'page-info'

Ambiguous method overloading for method `jdk.proxy279.$Proxy4022#hasContentLevelPermission`. Cannot resolve which method to invoke for `[null, class java.lang.String, class com.atlassian.confluence.pages.Page]` due to overlapping prototypes between: `[interface com.atlassian.confluence.user.ConfluenceUser, class java.lang.String, class com.atlassian.confluence.core.ContentEntityObject]` `[interface com.atlassian.user.User, class java.lang.String, class com.atlassian.confluence.core.ContentEntityObject]`