

TE0724 Test Board

Overview

Table of contents

Zynq PS Design with Linux Example and Virtual Input/Output (VIO) for Control and Monitoring with Vivado HW-Manager

Overview

Wiki Resources

Page Features

1.2 Revision History

1.3 Release Notes and Know Issues

1.4 Requirements

1.4.1 Software

1.4.2 Hardware

1.5 Content

1.5.1 Design Sources

1.5.2 Additional Sources

1.5.3 Prebuilt

1.5.4 Download

2 Design Flow

3 RTC

3.1 Launch

3.1.1 Programming

3.1.2 I2C Buffer for PMIC (RTC) and external I2C

3.1.3 QSPI-Boot mode

3.1.4 SD-Boot mode

3.2 Usage

3.2.1 Linux

3.2.2 Vivado HW Manager

4 System Design - Vivado

4.1 Block Design

4.1.1 PS Interfaces

4.2 Constrains

4.2.1 Basic module constraints

4.2.2 Design specific constraints

5 Software Design - Vitis

5.1 Application

5.1.1 zynq_fsbl

5.1.2 hello_te0724

6 Software Design - PetaLinux

6.1 Config

6.2 U-Boot

6.3 Device Tree

6.4 Kernel

6.5 Rootfs

6.6 FSBL patch (alternative for vito fsbl trenz patch)

6.7 Applications

6.7.1 startup

6.7.2 webfwu

7 Additional Software

8 Appx. A: Change History and Legal Notices

8.1 Document Change History

8.2 Legal Notices

8.3 Data Privacy

8.4 Document Warranty

8.5 Limitation of Liability

8.6 Copyright Notice

8.7 Technology Licenses

8.8 Environmental Protection

8.9 REACH, RoHS and WEEE

9 Table of contents

TE0724 Test Board

1738

Date	Project Built	Authors	Description
2023-08-11	TE0724-test_board-vivado_2022.2-build_4_202308111308	Manuela Strücker	- Release Vivado 2022.2 - new assembly variants
2022-11-16	TE0724-test_board-vivado_2021.2-build_20_20221119073924.zip	Manuela Strücker	- Release Vivado 2021.2.1 - script update - new assembly variants
2020-03-25	TE0724-test_board-vivado_2019.2-build_8_20200325075929.zip	John Hartfiel	script update
2020-01-30	TE0724-test_board-vivado_2019.2-build_4_20200130130053.zip	John Hartfiel	2019.2 update - Vitis support - FSBL changes - petalinux device tree and u-boot update

2019-13-12	2018.2	TE0724-test_board_noprebuilt-vivado_2018.2-build_04_20191212064015.zip TE0724-test_board-vivado_2018.2-build_04_20191212064001.zip	John Hartfiel	bugfix IO constrains
2019-06-13	2018.2	TE0724-test_board-vivado_2018.2-build_04_20190613114927.zip TE0724-test_board_noprebuilt-vivado_2018.2-build_04_20190613115049.zip	Oleksandr Kiyenko, John Hartfiel	add app to get access to EEPROM U10
2019-02-04	2018.2	TE0724-test_board-vivado_2018.2-build_04_20190204111543.zip TE0724-test_board_noprebuilt-vivado_2018.2-build_04_20190204111557.zip	John Hartfiel	- Important Board Part File Update - change DDR3 to DDR3 Low Power
2018-08-29	2018.2	TE0724-test_board_noprebuilt-vivado_2018.2-build_03_20180830170634.zip TE0724-test_board-vivado_2018.2-build_03_20180830170621.zip	John Hartfiel	initial release

Design Revision History

Release Notes and Know Issues

Issues	Description	Workaround	To be fixed version
EEPROM U10 is not writeable	WP is fix on on PCB Revisions, which shipped before 2019-06-13	PCB can be patched, send request to Trenz Electronic support	---

Known Issues

Requirements

Software

Software	Version	Note
Vitis	2022.2	needed Vivado is included into Vitis installation
PetaLinux	2022.2	needed

Software

Hardware

Basic description of TE Board Part Files is available on [TE Board Part Files](#).

Complete List is available on "<project folder>\board_files*_board_files.csv"

Design supports following modules:

Module Model	Board Part Short Name	PCB Revision Support	DDR	QSPI Flash	EMMC	Others	Notes
TE0724-02-10-1I	10_1i_1gb	REV02	1GB	32MB	NA	NA	NA
TE0724-02-20-1	20_1i_1gb	REV02	1GB	32MB	NA	NA	NA
TE0724-02-20-1IC1	20_1i_1gb	REV02	1GB	32MB	NA	NA	NA
TE0724-03-10-1I	10_1i_1gb	REV03	1GB	32MB	NA	NA	NA
TE0724-03-20-1I	20_1i_1gb	REV03	1GB	32MB	NA	NA	NA
TE0724-03-20-1IC1	20_1i_1gb	REV03	1GB	32MB	NA	NA	NA
TE0724-04-41I32-A	10_1i_1gb	REV04	1GB	32MB	NA	NA	NA
TE0724-04-41I33-A*	10_1i_1gb	REV04	1GB	64MB	NA	NA	NA
TE0724-04-41I33-AZ	10_1i_1gb	REV04	1GB	64MB	NA	NA	NA
TE0724-04-61I32-A	20_1i_1gb	REV04	1GB	32MB	NA	NA	NA
TE0724-04-61I32-AZ	20_1i_1gb	REV04	1GB	32MB	NA	NA	NA
TE0724-04-61I33-AC	20_1i_1gb	REV04	1GB	64MB	NA	NA	NA
TE0724-04-S001	10_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-S003	10_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-S004	10_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-S005	10_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-S008	10_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-S011C1	20_1i_1gb	REV04	1GB	64MB	NA	NA	CAO
TE0724-04-61I33-A	20_1i_1gb	REV04	1GB	64MB	NA	NA	NA

* used as reference

Hardware Modules

Design supports following carriers:

Carrier Model	Notes
TEB0724	

*used as reference

Hardware Carrier

Additional HW Requirements:

Additional Hardware	Notes

*used as reference

Additional Hardware

Content

For general structure and of the reference design, see [Project Delivery - AMD devices](#)

Design Sources

Type	Location	Notes
Vivado	<project folder>\block_design <project folder>\constraints <project folder>\ip_lib <project folder>\board_files	Vivado Project will be generated by TE Scripts
Vitis	<project folder>\sw_lib	Additional Software Template for Vitis and apps_list.csv with settings automatically for Vitis app generation
PetaLinux	<project folder>\os\petalinux	PetaLinux template with current configuration

Design sources

Additional Sources

Type	Location	Notes
init.sh	<project folder>\misc\sd	Additional Initialization Script for Linux

Additional design sources

Prebuilt

File	File-Extension	Description
BIF-File	*.bif	File with description to generate Bin-File

BIN-File	*.bin	Flash Configuration File with Boot-Image (Zynq-FPGAs)
BIT-File	*.bit	FPGA (PL Part) Configuration File
Boot Script-File	*.scr	Distro Boot Script file
DebugProbes-File	*.ltx	Definition File for Vivado/Vivado Labtools Debugging Interface
Diverse Reports	---	Report files in different formats
Device Tree	*.dts	Device tree (2 possible, one for u-boot and one for linux)
Hardware-Platform-Description-File	*.xsa	Exported Vivado hardware description file for Vitis and PetaLinux
LabTools Project-File	*.lpr	Vivado Labtools Project File
OS-Image	*.ub	Image with Linux Kernel (On Petalinux optional with Devicetree and RAM-Disk)
Software-Application-File	*.elf	Software Application for Zynq or MicroBlaze Processor Systems

Prebuilt files (only on ZIP with prebuilt content)

Download

Reference Design is only usable with the specified Vivado/Vitis/PetaLinux version. Do never use different Versions of Xilinx Software for the same Project.

Reference Design is available on:

- [TE0724 "Test Board" Reference Design](#)

Design Flow



Reference Design is available with and without prebuilt files. It's recommended to use TE prebuilt files for first launch.

Trenz Electronic provides a tcl based built environment based on Xilinx Design Flow.

See also:

- [AMD Development Tools#XilinxSoftware-BasicUserGuides](#)
- [Vivado Projects - TE Reference Design](#)
- [Project Delivery](#).

The Trenz Electronic FPGA Reference Designs are TCL-script based project. Command files for execution will be generated with "_create_win_setup.cmd" on Windows OS and "_create_linux_setup.sh" on Linux OS.

TE Scripts are only needed to generate the vivado project, all other additional steps are optional and can also executed by Xilinx Vivado/Vitis GUI. For currently Scripts limitations on Win and Linux OS see: [Project Delivery Currently limitations of functionality](#)



Caution! Win OS has a 260 character limit for path lengths which can affect the Vivado tools. To avoid this issue, use Virtual Drive or the shortest possible names and directory locations for the reference design (for example "x:\<project folder>")

TE Scripts are only needed to generate the vivado project, all other additional steps are optional and can also executed by Xilinx Vivado/SDK GUI. For currently Scripts limitations on Win and Linux OS see: [Project Delivery Currently limitations of functionality](#)

1. Run `_create_win_setup.cmd/_create_linux_setup.sh` and follow instructions on shell:

`_create_win_setup.cmd/_create_linux_setup.sh`

```
-----Set design paths-----
-- Run Design with: _create_win_setup
-- Use Design Path: <absolute project path>
-----
-----TE Reference Design-----
-----
-- (0) Module selection guide, project creation...prebuilt export...
-- (1) Create minimum setup of CMD-Files and exit Batch
-- (2) Create maximum setup of CMD-Files and exit Batch
-- (3) (internal only) Dev
-- (4) (internal only) Prod
-- (c) Go to CMD-File Generation (Manual setup)
-- (d) Go to Documentation (Web Documentation)
-- (g) Install Board Files from Xilinx Board Store (beta)
-- (a) Start design with unsupported Vivado Version (beta)
-- (x) Exit Batch (nothing is done!)
----
Select (ex.: '0' for module selection guide):
```

2. Press 0 and enter to start "Module Selection Guide"
3. Create project and follow instructions of the product selection guide, settings file will be configured automatically during this process.
 - optional for manual changes: Select correct device and Xilinx install path on "design_basic_settings.cmd" and create Vivado project with "vivado_create_project_gui mode.cmd"



Note: Select correct one, see also [Vivado Board Part Flow](#)

4. Create hardware description file (.xsa file) for PetaLinux project and export to prebuilt folder

run on Vivado TCL (Script generates design and export files into "<project folder>\prebuilt\hardware\<short name>")

```
TE::hw_build_design -export_prebuilt
```



Using Vivado GUI is the same, except file export to prebuilt folder.

5. Create and configure your PetaLinux project with exported .xsa-file, see [PetaLinux KICKstart](#)
 - use TE Template from "<project folder>\os\petalinux"
 - use exported .xsa file from "<project folder>\prebuilt\hardware\<short name>". **Note:** HW Export from Vivado GUI creates another path as default workspace.

- The build images are located in the "<plnx-proj-root>/images/linux" directory
6. Configure the **boot.scr** file as needed, see [Distro Boot with Boot.scr](#)
 7. Generate Programming Files with Vitis (recommended)
 - a. Copy PetaLinux build image files to prebuilt folder
 - copy **u-boot.elf**, **system.dtb**, **image.ub** and **boot.scr** from "<plnx-proj-root>/images/linux" to prebuilt folder



"<project folder>\prebuilt\os\petalinux\<ddr size>" or "<project folder>\prebuilt\os\petalinux\<short name>"

- b. Generate Programming Files with Vitis

run on Vivado TCL (Script generates applications and bootable files, which are defined in "test_board\sw_lib\apps_list.csv")

```
TE::sw_run_vitis -all
TE::sw_run_vitis (optional; Start Vitis from Vivado GUI or start with
TE Scripts on Vivado TCL)
```



TCL scripts generate also platform project, this must be done manually in case GUI is used. See [Vitis](#)

8. Generate Programming Files with Petalinux (alternative), see [PetaLinux KICKstart](#)

Launch

Programming



Check Module and Carrier TRMs for proper HW configuration before you try any design.

Reference Design is also available with prebuilt files. It's recommended to use TE prebuilt files for first launch.

Xilinx documentation for programming and debugging: [Vivado/Vitis/SDSoC-Xilinx Software Programming and Debugging](#)

Get prebuilt boot binaries

1. Run `_create_win_setup.cmd/_create_linux_setup.sh` and follow instructions on shell
2. Press 0 and enter to start "Module Selection Guide"
 - a. Select assembly version
 - b. Validate selection
 - c. Select Create and open delivery binary folder



Note: Folder "<project folder>_binaries_<Article Name>" with subfolder "boot_<app name>" for different applications will be generated

QSPI-Boot mode

Option for **Boot.bin** on QSPI Flash and **image.ub** and **boot.scr** on **SD** or **USB**.

1. Connect **JTAG** and power on carrier with module
2. Open Vivado Project with "vivado_open_existing_project_gui mode.cmd" or if not created, create with "vivado_create_project_gui mode.cmd"

run on Vivado TCL (Script programs BOOT.bin on QSPI flash)

```
TE::pr_program_flash -swapp u-boot
TE::pr_program_flash -swapp hello_te0724 (optional)
```

3. Copy **image.ub** and **boot.scr** on **SD** or **USB**
 - use files from "<project folder>_binaries_<Article Name>\boot_linux" from generated binary folder, see: [Get prebuilt boot binaries](#)
 - or use prebuilt file location, see "<project folder>\prebuilt\file_location.txt"
4. Set Boot Mode to **QSPI-Boot** and insert **SD** or **USB** card.
 - Depends on Carrier, see carrier TRM.

SD-Boot mode

1. Copy **image.ub**, **boot.src** and **Boot.bin** on **SD**
 - use files from "<project folder>_binaries_<Article Name>\boot_linux" from generated binary folder, see: [Get prebuilt boot binaries](#)
 - or use prebuilt file location, see "<project folder>\prebuilt\file_location.txt"
2. Set Boot Mode to SD-Boot.
 - Depends on Carrier, see carrier TRM.
3. Insert SD-Card in SD-Slot.

JTAG

Not used on this Example.

Usage

1. Prepare HW like described on section [Programming](#)
2. Connect UART USB (most cases same as JTAG)
3. Select SD Card or QSPI as Boot Mode (Depends on used programming variant)



Note: See TRM of the Carrier, which is used.



Starting with Petalinux version 2020.1, the industry standard "Distro-Boot" boot flow for U-Boot was introduced, which significantly expands the possibilities of the boot process and has the primary goal of making booting much more standardised and predictable. The boot options described above describe the common boot processes for this hardware; other boot options are possible. For more information see [Distro Boot with Boot.scr](#)

4. Power On PCB
 1. Zynq Boot ROM loads FSBL from SD/QSPI into OCM,
 2. FSBL init the PS, programs the PL using the bitstream and loads U-boot from SD/QSPI into DDR,
 3. U-boot loads Linux (**image.ub**) from SD/QSPI/... into DDR

Linux

1. Open Serial Console (e.g. putty)

- a. Speed: 115200
- b. Select COM Port



Win OS, see device manager, Linux OS see dmesg |grep tty (UART is *USB1)

2. Linux Console:

```
# password disabled
petalinux login: root
Password: root
```



Note: Wait until Linux boot finished

3. You can use Linux shell now.

```
I2C
    i2cdetect -l          (Shows a list of the available I2C buses)
    i2cdetect -y -r 0      (check I2C 0 Bus)
RTC
    dmesg | grep rtc       (RTC check)
ETH0
    udhcpc                 (ETH0 check)
GPIO
    gpiodetect             (list all gpiochips present on the
system)
    gpioget `gpiofind "MI051_J9-6"` (read value of
specified GPIO)
    gpioset `gpiofind "MI09_D8"`=1  (set value of specified
GPIO)
```

4. Option Features

- Webserver to get access to Zynq
 - insert IP on web browser to start web interface
- init.sh scripts
 - add init.sh script on SD, content will be load automatically on startup (template included in "<project folder>\misc\SD")

Vivado HW Manager

Open Vivado HW-Manager and add VIO signal to dashboard (*.ltx located on prebuilt folder)

- Control:
 - CAN_STBY[0:0] CAN Standby control
 - LED_RG[1:0] module LED control
 - TEB0724_ULED[5:0] TEB0724 LED control
- Monitoring:
 - vio_TEB0724_BUTTON_S24[1:0] TEB0724 Button S2 and S4
 - vio_PWR_GPIO01[1:0] PMIC GPIO
 - fm_PHY_CLK125M[31:0] PHY Clock 125MHz
 - labtools_fmeter_0_update FMeter Update

hw_vios					
Dashboard Options					

Type	Note
DDR	
QSPI	MIO
ETH0	MIO
SD0	MIO
UART1	MIO
I2C1	MIO
CAN0	EMIO
GPIO	MIO

TTC0..1	EMIO
WDT	EMIO

PS Interfaces

Constrains

Basic module constrains

_i_bitgen_common.xdc

```
#
# Common BITGEN related settings for TE0724 SoM
#
set_property BITSTREAM.GENERAL.COMPRESS TRUE [current_design]
set_property CONFIG_VOLTAGE 3.3 [current_design]
set_property CFGBVS VCC0 [current_design]
```

Design specific constrain

_i_io.xdc

```
# can
set_property PACKAGE_PIN T11 [get_ports CAN_0_tx]
set_property IOSTANDARD LVCMOS33 [get_ports CAN_0_tx]
set_property PACKAGE_PIN T10 [get_ports CAN_0_rx]
set_property IOSTANDARD LVCMOS33 [get_ports CAN_0_rx]
set_property PACKAGE_PIN U13 [get_ports {CAN_STBY[0]}]
set_property IOSTANDARD LVCMOS33 [get_ports {CAN_STBY[0]}]
# led
set_property PACKAGE_PIN U12 [get_ports {LED_RG[0]}]
set_property PACKAGE_PIN W13 [get_ports {LED_RG[1]}]
set_property IOSTANDARD LVCMOS33 [get_ports {LED_RG[*]}]
# CLK
set_property PACKAGE_PIN U14 [get_ports {PHY_CLK125M[0]}]
set_property IOSTANDARD LVCMOS33 [get_ports {PHY_CLK125M[0]}]
# PWR GPIO
set_property PACKAGE_PIN T12 [get_ports {PWR_GPIO01[0]}]
set_property PACKAGE_PIN U15 [get_ports {PWR_GPIO01[1]}]
set_property IOSTANDARD LVCMOS33 [get_ports {PWR_GPIO01[*]}]
# TEB0724 Button
set_property PACKAGE_PIN Y19 [get_ports {TEB0724_BUTTON_S24[0]}]
set_property PACKAGE_PIN Y18 [get_ports {TEB0724_BUTTON_S24[1]}]
set_property IOSTANDARD LVCMOS33 [get_ports {TEB0724_BUTTON_S24[*]}]
# TEB0724 LED
set_property PACKAGE_PIN P18 [get_ports {TEB0724_ULED[0]}]
set_property PACKAGE_PIN N17 [get_ports {TEB0724_ULED[1]}]
set_property PACKAGE_PIN R17 [get_ports {TEB0724_ULED[2]}]
set_property PACKAGE_PIN R16 [get_ports {TEB0724_ULED[3]}]
set_property PACKAGE_PIN Y14 [get_ports {TEB0724_ULED[4]}]
set_property PACKAGE_PIN W14 [get_ports {TEB0724_ULED[5]}]
set_property IOSTANDARD LVCMOS33 [get_ports {TEB0724_ULED[*]}]
```

Software Design - Vitis

For Vitis project creation, follow instructions from:

[Vitis](#)

Application

Template location: "<project folder>\sw_lib\sw_apps\"

zynq_fsbl

TE modified 2022.2 FSBL

General:

- Modified Files: main.c, fsbl_hooks.h/c (search for 'TE Mod' on source code)
- Add Files: te_fsbl_hooks.h/c (for hooks and board)
- General Changes:
 - Display FSBL Banner and Device ID

Module Specific:

- Add Files: all TE Files start with te_*
 - enable I2C voltage-level translator over MIO38. Needed for PMIC-RTC and external I2C.

hello_te0724

Hello TE0724 is a Xilinx Hello World example as endless loop instead of one console output.

u-boot

U-Boot.elf is generated with PetaLinux. Vitis is used to generate Boot.bin.

Software Design - PetaLinux

For PetaLinux installation and project creation, follow instructions from:

- [PetaLinux KICKstart](#)

Config

Start with **petalinux-config** or **petalinux-config --get-hw-description**

Changes:

- add new flash partition for bootscr and sizing
 - CONFIG_SUBSYSTEM_FLASH_PSU_QSPI_0_BANKLESS_PART0_SIZE=0xA00000
 - CONFIG_SUBSYSTEM_FLASH_PSU_QSPI_0_BANKLESS_PART1_SIZE=0x1400000
 - CONFIG_SUBSYSTEM_FLASH_PSU_QSPI_0_BANKLESS_PART2_SIZE=0x20000
 - CONFIG_SUBSYSTEM_FLASH_PSU_QSPI_0_BANKLESS_PART3_NAME="bootscr"
 - CONFIG_SUBSYSTEM_FLASH_PSU_QSPI_0_BANKLESS_PART3_SIZE=0x40000
- Identification
 - CONFIG_SUBSYSTEM_HOSTNAME="Trenz"
 - CONFIG_SUBSYSTEM_PRODUCT="TE0724"
- MAC from eeprom together with uboot and device tree settings:
 - CONFIG_SUBSYSTEM_ETHERNET_PS7_ETHERNET_0_MAC_AUTO is not set

- ```
o CONFIG_SUBSYSTEM_ETHERNET_PS7_ETHERNET_0_MAC=""
```

## U-Boot

Start with **petalinux-config -c u-boot**

Changes:

- MAC from eeprom together with uboot and device tree settings:
  - CONFIG\_ENV\_OVERWRITE=y
  - CONFIG\_NET\_RANDOM\_ETHADDR is not set
- Boot Modes:
  - CONFIG\_QSPI\_BOOT=y
  - CONFIG\_SD\_BOOT=y
  - CONFIG\_ENV\_IS\_IN\_FAT is not set
  - CONFIG\_ENV\_IS\_IN\_NAND is not set
  - CONFIG\_ENV\_IS\_IN\_SPI\_FLASH is not set
  - CONFIG\_SYS\_REDUNDAND\_ENVIRONMENT is not set
  - CONFIG\_BOOT\_SCRIPT\_OFFSET=0x1E20000
- Identification
  - CONFIG\_IDENT\_STRING=" TE0724"

Change platform-top.h:

```
#include <configs/zynq-common.h>
#no changes
```

## Device Tree

```
project-spec\meta-user\recipes-bsp\device-tree\files\system-user.dtsi
```

```

/include/ "system-conf.dtsi"

/*----- default -----*/

/*----- GPIO -----*/
&gpio0 {
 gpio-line-names =
 "MI00_PWR" , "" , "" , "" ,
 "" , "" , "MI07" , "" ,
"MI09_D8" ,
"MI010_J7-5" , "MI011_J7-6" , "MI012_J7-7" , "MI013_J7-8" , "MI014_J7-
9" ,
 "MI015_J7-10" , "" , "" , "" ,
 "" , "" , "" , "" ,
 "" , "" , "" , "" ,
 "MI030_nC" , "MI031_nC" , "MI032_nC" , "MI033_nC" ,
"MI034_nC" ,
 "MI035_nC" , "MI036_nC" , "MI037_nC" , "MI038_TCA-0E" ,
 "" , "" , "" , "" ,
 "" ,

```

```

 "" , "MI046_J9-4" , "" , "" ,
"" ,
 "MI050_J9-5" , "MI051_J9-6" , "" , "" ;
};

/*----- QSPI -----*/
&qspi {
 is-dual = <0>;
 num-cs = <1>;
 #address-cells = <1>;
 #size-cells = <0>;
 status = "okay";
 spi-rx-bus-width = <4>;
 flash@0 {
 compatible = "jedec,spi-nor";
 reg = <0x0>;
 #address-cells = <1>;
 #size-cells = <1>;
 spi-rx-bus-width = <4>;
 };
};

/*----- ETH PHY -----*/
&gem0 {
 /delete-property/ local-mac-address;
 phy-handle = <&phy0>;

 nvmem-cells = <ð0_addr>;
 nvmem-cell-names = "mac-address";

 phy0: phy@0 {
 device_type = "ethernet-phy";
 reg = <1>;
 };
};

/*----- I2C -----*/
&i2c1 {

 //pmic
 pmic@da9062@58 {
 compatible = "dlg,da9062";
 reg = <0x58>;
 interrupt-parent = <&gpio0>;
 interrupts = <0 8>;
 interrupt-controller;
 rtc {
 compatible = "dlg,da9062-rtc";
 };
 };

 //MAC EEPROM
 eeprom: eeprom@53 {
 compatible = "microchip,24aa025", "atmel,24c02";
 reg = <0x53>;

 #address-cells = <1>;
 #size-cells = <1>;
 eth0_addr: eth-mac-addr@FA {
 reg = <0xFA 0x06>;
 };
 };
};

```

```
};

//user EEPROM
eeprom50: eeprom@50 {
 compatible = "microchip,24aa128", "atmel,24c128";
 reg = <0x50>;
};

};
```

## Kernel

Start with **petalinux-config -c kernel**

Changes:

- CONFIG\_REGMAP\_IRQ=y
- # CONFIG\_PINCTRL\_DA9062 is not set
- # CONFIG\_DA9062\_THERMAL is not set
- # CONFIG\_DA9062\_WATCHDOG is not set
- CONFIG\_MFD\_DA9062=y
- # CONFIG\_REGULATOR\_DA9062 is not set
- CONFIG\_RTC\_DRV\_DA9063=y

## Rootfs

Start with **petalinux-config -c rootfs**

Changes:

- For web server app:
  - CONFIG\_busybox-httpd=y
- For additional test tools only:
  - CONFIG\_i2c-tools=y
  - CONFIG\_packagegroup-petalinux-utils=y (util-linux,cpufrequtils,bridge-utils,mtd-utils,usbutils,pciutils,canutils,i2c-tools,smartmontools,e2fsprogs)
- For use of libgpod-tools (gpiodetect, gpioset, gpioget, ...) together with device tree settings:
  - CONFIG\_libgpod-tools=y
- For auto login:
  - CONFIG\_auto-login=y
  - CONFIG\_ADD\_EXTRA\_USERS="root:root;petalinux:;"

Add in <project folder>\os\petalinux\project-spec\meta-user\conf\user-rootfsconfig

```
CONFIG_libgpod-tools
```

## FSBL patch (alternative for vitis fsbl trenz patch)

See "<project folder>\os\petalinux\project-spec\meta-user\recipes-bsp\embeddedsw"

## Applications

See "<project folder>\os\petalinux\project-spec\meta-user\recipes-apps"

## startup

Script App to load init.sh from SD Card if available.

## webfwu

Webserver application suitable for Zynq access. Need busybox-httpd

## Additional Software

No additional software is needed.

## Appx. A: Change History and Legal Notices

### Document Change History

To get content of older revision go to "Change History" of this page and select older document revision number.

| Date                                                                                                                                                                                                                                              | Document Revision                                                                                                                                                                                                                                 | Authors                                                                                                                                                                                                                                           | Description                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| <div>Error<br/>rendering<br/>macro<br/>'page-info'<br/><br/>Ambiguous<br/>method<br/>overloading<br/>for method<br/>jdk.<br/>proxy279.\$P<br/>roxy4022#h<br/>asContentLe<br/>velPermissio<br/>n. Cannot<br/>resolve<br/>which<br/>method to</div> | <div>Error<br/>rendering<br/>macro<br/>'page-info'<br/><br/>Ambiguous<br/>method<br/>overloading<br/>for method<br/>jdk.<br/>proxy279.\$P<br/>roxy4022#h<br/>asContentLe<br/>velPermissio<br/>n. Cannot<br/>resolve<br/>which<br/>method to</div> | <div>Error<br/>rendering<br/>macro<br/>'page-info'<br/><br/>Ambiguous<br/>method<br/>overloading<br/>for method<br/>jdk.<br/>proxy279.\$P<br/>roxy4022#h<br/>asContentLe<br/>velPermissio<br/>n. Cannot<br/>resolve<br/>which<br/>method to</div> | <ul style="list-style-type: none"><li>• Release Vivado 2022.2</li><li>• new assembly variants</li></ul> |



invoke for  
[null, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
pages.  
Page] due  
to  
overlapping  
prototypes  
between:  
[interface  
com.  
atlassian.  
confluence.  
user.  
Confluence  
User, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit  
yObject]  
[interface  
com.  
atlassian.  
user.User,  
class java.  
lang.String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit

invoke for  
[null, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
pages.  
Page] due  
to  
overlapping  
prototypes  
between:  
[interface  
com.  
atlassian.  
confluence.  
user.  
Confluence  
User, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit  
yObject]  
[interface  
com.  
atlassian.  
user.User,  
class java.  
lang.String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit

invoke for  
[null, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
pages.  
Page] due  
to  
overlapping  
prototypes  
between:  
[interface  
com.  
atlassian.  
confluence.  
user.  
Confluence  
User, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit  
yObject]  
[interface  
com.  
atlassian.  
user.User,  
class java.  
lang.String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit

| yObject]   | yObject] | yObject]                                                                                                                                                                                                                                                    |                                                                                                                                       |
|------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| 2022-11-21 | v.12     | Manuela Strücker                                                                                                                                                                                                                                            | <ul style="list-style-type: none"> <li>• Release Vivado 2021.2.1</li> <li>• script update</li> <li>• new assembly variants</li> </ul> |
| 2020-03-25 | v.10     | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• script update</li> </ul>                                                                     |
| 2020-01-30 | v.9      | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• Release 2019.2</li> <li>• document style update</li> </ul>                                   |
| 2019-12-12 | v.8      | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• Bugfix IO constrains</li> </ul>                                                              |
| 2019-06-13 | v.7      | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• Update Design Files</li> <li>• Notes U10 access</li> </ul>                                   |
| 2019-02-04 | v.6      | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• Update Design Files</li> </ul>                                                               |
| 2018-08-30 | v.5      | John Hartfiel                                                                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>• 2018.2 release</li> </ul>                                                                    |
| --         | all      | <div> <p><b>Error rendering macro 'page-info'</b></p> <p>Ambiguous method overloading for method jdk.<br/> proxy279.\$P<br/> roxy4022#h<br/> asContentLe<br/> velPermissio<br/> n. Cannot<br/> resolve<br/> which<br/> method to<br/> invoke for</p> </div> | --                                                                                                                                    |

[null, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
pages.  
Page] due  
to  
overlapping  
prototypes  
between:  
[interface  
com.  
atlassian.  
confluence.  
user.  
Confluence  
User, class  
java.lang.  
String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit  
yObject]  
[interface  
com.  
atlassian.  
user.User,  
class java.  
lang.String,  
class com.  
atlassian.  
confluence.  
core.  
ContentEntit  
yObject]

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|--|--|--|--|

Document change history.

## Legal Notices

### Data Privacy

Please also note our data protection declaration at <https://www.trenz-electronic.de/en/Data-protection-Privacy>

### Document Warranty

The material contained in this document is provided “as is” and is subject to being changed at any time without notice. Trenz Electronic does not warrant the accuracy and completeness of the materials in this document. Further, to the maximum extent permitted by applicable law, Trenz Electronic disclaims all warranties, either express or implied, with regard to this document and any information contained herein, including but not limited to the implied warranties of merchantability, fitness for a particular purpose or non infringement of intellectual property. Trenz Electronic shall not be liable for errors or for incidental or consequential damages in connection with the furnishing, use, or performance of this document or of any information contained herein.

### Limitation of Liability

In no event will Trenz Electronic, its suppliers, or other third parties mentioned in this document be liable for any damages whatsoever (including, without limitation, those resulting from lost profits, lost data or business interruption) arising out of the use, inability to use, or the results of use of this document, any documents linked to this document, or the materials or information contained at any or all such documents. If your use of the materials or information from this document results in the need for servicing, repair or correction of equipment or data, you assume all costs thereof.

### Copyright Notice

No part of this manual may be reproduced in any form or by any means (including electronic storage and retrieval or translation into a foreign language) without prior agreement and written consent from Trenz Electronic.

### Technology Licenses

The hardware / firmware / software described in this document are furnished under a license and may be used /modified / copied only in accordance with the terms of such license.

### Environmental Protection

To confront directly with the responsibility toward the environment, the global community and eventually also oneself. Such a resolution should be integral part not only of everybody's life. Also enterprises shall be conscious of their social responsibility and contribute to the preservation of our common living space. That is why Trenz Electronic invests in the protection of our Environment.

### REACH, RoHS and WEEE

REACH

Trenz Electronic is a manufacturer and a distributor of electronic products. It is therefore a so called downstream user in the sense of [REACH](#). The products we supply to you are solely non-chemical products (goods). Moreover and under normal and reasonably foreseeable circumstances of application, the goods supplied to you shall not release any substance. For that, Trenz Electronic is obliged to neither register nor to provide safety data sheet. According to present knowledge and to best of our knowledge, no [SVHC \(Substances of Very High Concern\) on the Candidate List](#) are contained in our products. Furthermore, we will immediately and unsolicited inform our customers in compliance with REACH - Article 33 if any substance present in our goods (above a concentration of 0,1 % weight by weight) will be classified as SVHC by the [European Chemicals Agency \(ECHA\)](#).

## RoHS

Trenz Electronic GmbH herewith declares that all its products are developed, manufactured and distributed RoHS compliant.

## WEEE

Information for users within the European Union in accordance with Directive 2002/96/EC of the European Parliament and of the Council of 27 January 2003 on waste electrical and electronic equipment (WEEE).

Users of electrical and electronic equipment in private households are required not to dispose of waste electrical and electronic equipment as unsorted municipal waste and to collect such waste electrical and electronic equipment separately. By the 13 August 2005, Member States shall have ensured that systems are set up allowing final holders and distributors to return waste electrical and electronic equipment at least free of charge. Member States shall ensure the availability and accessibility of the necessary collection facilities. Separate collection is the precondition to ensure specific treatment and recycling of waste electrical and electronic equipment and is necessary to achieve the chosen level of protection of human health and the environment in the European Union. Consumers have to actively contribute to the success of such collection and the return of waste electrical and electronic equipment. Presence of hazardous substances in electrical and electronic equipment results in potential effects on the environment and human health. The symbol consisting of the crossed-out wheeled bin indicates separate collection for waste electrical and electronic equipment.

Trenz Electronic is registered under WEEE-Reg.-Nr. DE97922676.

### Error rendering macro 'page-info'

Ambiguous method overloading for method `jdk.proxy279.$Proxy4022#hasContentLevelPermission`.  
Cannot resolve which method to invoke for `[null, class java.lang.String, class com.atlassian.confluence.pages.Page]` due to overlapping prototypes between: `[interface com.atlassian.confluence.user.ConfluenceUser, class java.lang.String, class com.atlassian.confluence.core.ContentEntityObject]`  
`[interface com.atlassian.user.User, class java.lang.String, class com.atlassian.confluence.core.ContentEntityObject]`